



### TRITTICO STARTRONIC PREMIUM

THE FIRST AND ORIGINAL MULTIFUNCTIONAL GELATO EQUIPMENT.  
SINCE 1974, 30 YEARS OF PATENTED EXPERIENCE.



### TRITTICO STARTRONIC PLUS

AN EXCLUSIVE SOFTWARE AND DIFFERENT SPEEDS ACCORDING  
TO EACH WORKING PHASE, TO OBTAIN A CREAMY AND DRY  
GELATO, WITH REGULAR STRUCTURE AND VERY THIN ICE CRYSTALS.

TECHNICAL SPECIFICATIONS		MODEL															
		122		183		204		305		457		610		1015		1020	
Capacity per cycle	Lt.	2		3		4		5		7,5		10		15		20	
Average hourly production (1)	Lt.	8/12		12/18		15/20		20/30		30/45		45/60		60/80		80/120	
Voltage (2)	Volt/Hz/Ph	230/50/1		400/50/3		400/50/3		400/50/3		400/50/3		400/50/3		400/50/3		400/50/3	
Power	Kw	3,2		5,3		5,3		5,8		6,3		9		11,2		18,3	
Refrigeraton condenser		Water	Air+Water	Water	Air+Water	Water	Air+Water	Water	Air+Water	Water	Air+Water	Water	Air+Water	Water	Air	Water	Air
Width (A)	cm.	36	36	50	50	50	50	50	50	50	60	60	60	60	60	60	60
Length (B)	cm.	59	59	70	70	65	65	65	65	80	80	80	80	85	85	100	100
Height (H)	cm.	63	63	72	72	130	130	130	130	130	130	130	130	130	130	130	130
Weight	Kg	105	105	150	150	248	268	270	290	290	310	390	440	450	510	520	590

(1) Hourly production may change according to type of mixture and finished product density. (2) Also available in 230 Volt/60Hz. Models 122, 204, 457 e 1015 are available in some countries only.



Bravo spa

Via della Tecnica, 5

36075 Montecchio Maggiore

Vicenza - Italy

Tel +39 0444 707700

Fax +39 0444 499333

www.bravo.it - bravo@bravo.it

www.bravo.it